FLEXIBLE PRINTED CIRCUIT BOARD CONNECTORS 📳 📼 🖃 👺 🔯




















Plugging system for FFC cables, wire-to-board and wire-to-wire connections. Preparation of jumpers and FFC cables with film crimp contacts from different manufacturers.

Quick assembly

FLEXCRIMP

- Compact and detachable connections
- Solder joints possible
- Pitches 1.27 mm (0.050") and 2.54 mm (0.100")
- Tin-plated or gold-plated crimp contacts

MANUFACTURERS

Preferentially, plug-in connectors from **TE Connectivity (Tyco)** are used. Nikomatic and FCI-connectors are also possible.

CONTACTS

Product numbers of contacts preferentially used by TE Connectivity (Tyco).

PITCH	1.27 mm (0.050")	2.54 mm (0.100")
Female contact	1 - 487547 - 1 (gold-plated)	2 - 487406 - 3 (gold-plated) 2 - 487406 - 4 (tin-plated)
Male contact	-	88117 - 7 (tin-plated)
Soldering pin	487923 - 4	1 - 88997 - 2 (tin-plated)

Further contacts available on request.

Housings

A wide range of housings is possible.

Examples of the most common TE Connectivity (Tyco) housing types are given in the table below:

PITCH	1.27 mm (0.050")	2.54 mm (0.100")	
without interlock	X - 487544 - X	X - 88859 - X	
with interlock	X - 487545 - X	X - 487526 - X	

X varies according to the number of poles. | We are pleased to advise you on the selection of products.

